

526032

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



28 FEB 2005



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/018733 A2

- (51) International Patent Classification⁷: **C25B**
- (21) International Application Number:
PCT/NO2003/000296
- (22) International Filing Date: 26 August 2003 (26.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20024054 26 August 2002 (26.08.2002) NO
- (71) Applicant (*for all designated States except US*): **ORO AS** [NO/NO]; Postboks 23, Kristianborg, N-5822 Bergen (NO).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **BELT, Jarle** [—/NO]; Sagvågsveien 233, N-5410 Sagvåg (NO).
- (74) Agent: **AS BERGEN PATENTKONTOR**; P.O. Box 1998, Nordnes, N-5817 Bergen (NO).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: STRUCTURE OF AN ELECTRODE FOR USE IN AN ELECTROLYTIC CELL

(57) Abstract: There is disclosed a structure of an electrode for use as an anode and/or a cathode in an electrolytic cell. The electrode structure is characterised by a conductive frame (10) having a number of liquid through flow openings (18) and including means (20) for connection to current a supply, in that one or both plane sides of the frame is covered with a conductive perforated foil or a wire mesh, and the wire mesh includes spacer means (18) being adapted to cover the surface structure of the frame (10). A method for preparing said electrode and use of the anode and cathode are also disclosed.

WO 2004/018733 A2